

# CERTIFICATE

No. 2004437-35



**DANISH  
TECHNOLOGICAL  
INSTITUTE**

Gregersensvej  
DK-2630 Taastrup  
Tel. +45 72 20 20 00  
Fax +45 72 20 20 19

info@teknologisk.dk  
www.teknologisk.dk

**Assignor:** Akzo Nobel Industrial Coatings  
Staffantörpvägen 50, Sege  
SE-205 17 Malmö  
Sweden

**Material:** H-Flex P. Spraying 171 (162-180) g/m<sup>2</sup>  
Rubbol WF 33xx. Spraying 131 (124-137) g/m<sup>2</sup>

**Method(s):** Test according to:  
EN 927-3:2012. Paints and varnishes - Coating materials and coating systems for exterior wood - Part 3: Natural weathering test.  
Deviation from method: Fine sawn Norway spruce is used as substrate.  
  
EN 927-5:2006. Paints and varnishes - Coating materials and coating systems for exterior wood - Part 5: Assessment of the liquid water permeability.  
  
Assessment according to:  
CMP – Certifierad Målad Panel. Certifieringsregler för industriellt ytbehandlade utvändiga panelbrädor. Version 9.3. 2015-12-21. 4.3.2 Krav på färger och färgsystem.

**Report No(s):** EN 927-5: 777838-1 dated 20-12-2017  
EN 927-3: 777838-05 dated 20-12-2018

**Conclusion:** The exposure conditions are rated as 'medium' and the system under test is considered as 'mould resistant' and can be categorized as 'Stable'.

**Date/Place:** 21-12-2018 Danish Technological Institute, Wood and Biomaterials, Taastrup

**Signature:** Responsible Co-signatory