

CERTIFICATE

No. 2004437-38



**DANISH
TECHNOLOGICAL
INSTITUTE**

Gregersensvej
DK-2630 Taastrup
Tel. +45 72 20 20 00
Fax +45 72 20 20 19

info@teknologisk.dk
www.teknologisk.dk

Assignor: Akzo Nobel Industrial Coatings
Staffantörpvägen 50, Sege
SE-205 17 Malmö
Sweden

Material: Rubbol WF 33xx. Spraying 131 (124-137) g/m²
Rubbol WF 33xx. Spraying 131 (124-137) g/m²

Method(s): Test according to:
EN 927-3:2012. Paints and varnishes - Coating materials and coating systems for exterior wood - Part 3: Natural weathering test.
Deviation from method: Fine sawn Norway spruce is used as substrate.

EN 927-5:2006. Paints and varnishes - Coating materials and coating systems for exterior wood - Part 5: Assessment of the liquid water permeability.

Assessment according to:
CMP – Certifierad Målad Panel. Certifieringsregler för industriellt ytbehandlade utvändiga panelbrädor. Version 9.3. 2015-12-21. 4.3.2 Krav på färger och färgsystem.

Report No(s): EN 927-5: 777838-4 dated 20-12-2017
EN 927-3: 777838-08 dated 20-12-2018

Conclusion: The exposure conditions are rated as 'medium' and the system under test is considered as 'mould resistant' and can be categorized as 'Stable'.

Date/Place: 21-12-2018 Danish Technological Institute, Wood and Biomaterials, Taastrup

Signature: Responsible Co-signatory